1	COMPTNED INDEDENDENT AUDIO	13.22	Magnetic field generating
1	COMBINED INDEPENDENT AUDIO SYSTEMS		circuit
2	.Changeover between audio systems	13.23	Conductor coil
3	Fading between plural signals	13.24	Light beam generation
4	.Combining signals to form	13.25	Overwriting
-	composite (e.g., mixing)	13.26	Setting light beam power level
5	One of systems having plural	13.27	Based on referenced test
3	concurrent signals (e.g.,		signal
	stereophonic)	13.28	Multiple light beams
6	.Radio	13.29	Polarized light beam
7	Including recording from radio	13.3	Plural polarization
8	Oscillator modulated by	13.31	Linear polarization
O	retrieved information signal	13.32	Light beam transducer assembly
9	Mechanical phonograph	13.33	Near field optic
10	With common cabinet for	13.34	In compact size assembly
10	cartridge or cassette	13.35	Specific detail of recording
11	Including separable assembly		medium
12	Cabinet details	13.36	In protective jacket
13.01	STORAGE OR RETRIEVAL BY	13.37	Tape or card
13.01	SIMULTANEOUS APPLICATION OF	13.38	Specific detail of layer
	DIVERSE TYPES OF	13.30	(e.g., bias or initializing
	ELECTROMAGNETIC RADIATION		layers, etc.)
13.02	.Magnetic field and light beam	13.39	Plural distinct storage
13.02	Initializing		layers
13.04	Erasing	13.4	Plural layers having
13.05	Reading		particular order
13.06	By transferring magnetic	13.41	Plural magnetic layers (e.g.,
13.00	domain between layers		recording and reproducing
13.07	Three or more magnetic layers		layers)
13.07	Changing size of magnetic	13.42	Three or more magnetic
13.00	domain		layers (e.g., recording,
13.09	Changing size of magnetic		intermediate, and reproducing
13.05	domain		layers, etc.)
13.1	Three or more magnetic states	13.43	In-plane magnetization
13.11	Positioning of transducer		layer
13.11	assembly for storage or	13.44	Exchange-coupling
	retrieval		magnetization layer
13.12	Relative positioning of	13.45	Rare earth or metal alloy
13,11	transducer assemblies	13.46	Temperature or coercivity
13.13	Integral transducers	13.47	Magnetic domain wall
13.14	Magnetic field generation	13.48	In-plane magnetization layer
13.15	Leakage magnetic field	13.49	Exchange-coupling
13.16	Overwriting		magnetization layer
13.17	Magnetic field transducer	13.5	Rare earth or metal alloy
	assembly	13.51	Temperature or coercivity
13.18	Permanent magnet	13.52	Magnetic domain wall
13.19	Rotating magnet	13.53	Thickness of layer
13.2	Operative location	13.54	Recording mark dimension
	positioning of transducer	13.55	Land or groove track
	assembly	13.56	STORAGE DIFFERENT FROM RETRIEVAL
13.21	During load and unload of		(E.G., OPTICAL RECORDING AND
	storage medium		MAGNETIC REPRODUCTION)
		300	DETAIL OF OPTICAL SLIDER PER SE

14	SIMULTANEOUS DIVERSE TYPES OF STORAGE OR RETRIEVAL	30.09	Specified order of contents information modification
15	ALTERNATIVE DIVERSE TYPES OF	20 1	processing
16	STORAGE OR RETRIEVAL MECHANICAL PRODUCTION OF OPTICAL STORAGE TRACK	30.1	Transducer movement control using recorded information indicative of location of
17	TRACK CONVERSION		<pre>information (e.g., track address)</pre>
18	OPTICAL READING OF MECHANICAL RECORD	30.11	Location information correction
Class 36	50 is an integral part of this	30.12	Particular track portion
tion of	Class 369), as shown by the posithis box, and follows the schedule	30.13	Counting tracks traversed by transducer
	ny of this Class, retaining all	30.14	Count correction
pertiner this cla	nt definitions and Class lines of ass.	30.15	Multiple movement control modes
		30.16	<pre>Specific detail of terminating</pre>
		30.17	Transducer velocity control
19	CONTROL BY TIMER OR EXTERNAL EXTRANEOUS CONDITION	30.18	Electrical information signal processing
20	.By diverse art device	30.19	Copying or editing
21	In vehicle or elevator	30.2	Plural storage medium
22	Audible indicator	20.01	elements
23	Talking clock	30.21	Monitoring signal error or
24.01	INFORMATION LOCATION OR REMOTE OPERATOR ACTUATED CONTROL	30.22	verificationCorrection of error
25.01	.Dictation or transcribing	30.22	Buffering
26.01	Privacy	30.23	Abnormal condition or
27.01	With access to or marking of	30.21	changing mode of system
27.01	specified location (e.g.,	30.25	Auxiliary information
	indexing)	30.26	Remote operating mode control
28.01	By stored additional signal (e.g., tone)	30.27	Electrical control signal processing
29.01	Remote station	30.28	Plural storage medium
29.02	Portable device		elements
30.01	<pre>.Selective addressing of storage medium (e.g., programmed access)</pre>	30.29	<pre>Matching control signalOf information indicative of contents or particular order</pre>
30.02	<pre>Novelty device (e.g., talking doll)</pre>	30.31	of contentsFor operation of storage
30.03	Of optical storage medium		medium gripper, accessor, or
30.04	Using recorded information		transfer member
	indicative of storage medium contents	30.32	<pre>For record medium loading or ejecting</pre>
30.05	Copying or editing	30.33	For radial array positioning
30.06	<pre>Plural storage medium elements (e.g., "juke box")</pre>		of unitary plural storage medium carrier
30.07	<pre>Specified contents information modification processing</pre>	30.34	<pre>For linear array positioning of unitary plural storage medium carrier (e.g.,</pre>
30.08	<pre>Designating particular order of contents (e.g., sequential playing back by playlist)</pre>		horizontal or vertical positioning)

30.35	For relative positioning between storage medium	30.65	Plural media are discs stored in cartridges
	elements	30.66	Having specified stocker or
30.36	Abnormal condition or		internal magazine
30.37	changing mode of systemOf particular order of	30.67	Stocker or internal magazine is adjustable or movable
	contents	30.68	Having particular removable
30.38	Plural optical storage media		magazine
	in library system	30.69	Mounting or locking magazine
30.39	Modular library system		to disc changer
30.4	Plural media are discs stored	30.7	Having particular internal
	in cartridges		transfer mechanism for
30.41	Having specified disk rack		transferring disc while disc
30.42	Having particular removable		is inside of disc changer
	magazine	30.71	Of carousel changer
30.43	Having specified picker	30.72	Having particular internal
30.44	Of carousel library system		support structure for internal
30.45	Picker support structure		transfer mechanism
	(i.e., mechanism for moving	30.73	Having specified drive
	picker)	30.74	Movable drive
30.46	Having specified disc drive	30.75	Having particular mechanism
30.47	Drive moves into alignment		or slot for transferring disc
	with disc		into changer from outside
30.48	Having particular mechanism	30.76	Plural media are unprotected
	or slot for transferring disc into library from outside		<pre>(i.e., discs that are not in cartridges)</pre>
30.49	Linear vertical or	30.77	Having specified stocker or
	horizontal array		internal magazine
30.5	Carousel array	30.78	Stocker or internal magazine
30.51	Plural media are unprotected		is adjustable or movable
	(i.e., discs that are not in	30.79	In carousel changer
	cartridges)	30.8	Positioning mechanism
30.52	Having specified disk rack	30.81	Having disc reproduced while
30.53	Having particular removable		entirely in magazine
	magazine	30.82	Having disc reproduced while
30.54	Mounting or locking magazine		partially in magazine
	to library system	30.83	Having particular removable
30.55	Having specified picker		magazine
30.56	Of carousel library system	30.84	Mounting or locking magazine
30.57	Picker support structure	20.05	to disc changer
	detail (i.e., mechanism for	30.85	Having particular internal
20 50	moving picker)		transfer mechanism for
30.58	Having specified disc drive		transferring disc while disc
30.59	Drive moves into alignment	30.86	is inside of disc changer
20 6	with disc	30.80	Of carousel changer
30.6	Having particular mechanism	30.67	Having specified internal support structure for internal
	or slot for transferring disc		transfer mechanism
20 61	into library from outside	30.88	Having specified drive
30.61	Linear vertical or	30.89	Movable drive
30.62	horizontal arrayCarousel array	30.0	Having particular mechanism
30.62	Having particular cabinet	50.5	or slot for transferring disc
30.63	Having particular capinetPlural optical storage media		into changer from outside
JU.U4	in disc changer	30.91	Of carousel changer
	In albe changer	30.92	Plural trays
			<u>-</u>

30.93	One tray for multiple discs	44.22	Lens or mirror floats, (e.g.,
30.94	Loading mechanism		magnetic field support or
30.95	Chucking mechanism		lens/mirror can freely float
30.96	Locking mechanism		and pivot about its own axis,
30.97	Positioning mechanism		etc.)
30.98		44.23	Structure for shaping beam or
30.90			causing astigmatic condition
20.00	drives multiple mechanisms	44.24	Means to mask or shield a
30.99	One tray for single disc	11.21	portion of the beam
31.01	Having particular cabinet	44.25	Servo signal compared to a
32.01	Specified electrical information signal processing	44.25	reference signal
33.01		44.26	Servo system operation related
33.01	Specified electrical control	11.20	to disc structure information
24 01	signal processing		format
34.01	Plural storage medium elements	44.27	Initialization/start-up or
35.01	Plural nontranslating storage	11.27	changing modes of system
	elements (e.g., in situ)	44.28	
36.01	Unitary plural record carrier	44.20	While track jumping or
37.01	Radial array		crossing
38.01	Moving linear array	44.29	Servo loop gain/switching
39.01	Scanning turntable		control
40.01	By manually actuated mechanism	44.31	Recording
	for movement of tone arm	44.32	Means to compensate for defect
41.01	Of track on single storage		or abnormal condition
11.01	medium	44.33	Recording (e.g., inhibit
42.01	.By mechanical linkage		recording upon defect, etc.)
43	WITH SERVO POSITIONING OF	44.34	Sampling servo system
43		44.35	Servo loop gain/switching
	TRANSDUCER ASSEMBLY OVER TRACK		control
	COMBINED WITH INFORMATION	44.36	Variable gain
44 11	SIGNAL PROCESSING	44.37	Plural incident beams
44.11	.Optical servo system	44.38	Recording
44.12	Solid state optical element	44.39	_
	with plural dissimilar optical		Recording
	components (e.g., using I.C.	44.41	Arithmetic operation using
	block, etc.)		plural photodetectors
44.13	Dithering or wobbling the beam	44.42	Beam or detector is not
	or track		rectangular or circular
44.14	Optical head servo system	47.1	CONTROL OF STORAGE OR RETRIEVAL
	structure		OPERATION BY A CONTROL SIGNAL
44.15	Elastic, flexible, pliant or		TO BE RECORDED OR REPRODUCED
	spring support of lens or	47.11	.Control of initiation of pause
	mirror		mode
44.16	Flat flexible support (e.g.,	47.12	.For copying
	parallel leaf spring, etc.)	47.13	.For editing
44.17	Optical head element with	47.14	.By medium defect indicative
	rotary motion		control signal
44.18	Rotary head wheel or scanner	47.15	.Control of information signal
11.10	(e.g., for use with arcuate,	1,,120	processing channel
	transverse or slant tracks,	47.16	of plural interrelated channels
	etc.)	47.10	For removal of unwanted signal
44.19		五/• ⊥/	
11. 17	Head element pivots on arm	47 10	component
	(e.g., optical head disk arm	47.18	For interpolating or drop-out
44 01	etc)	45 10	correcting
44.21	Lens or mirror pivots off	47.19	For modulating or demodulating
	center (e.g., on a shaft,	47.2	For multiplexing or
	etc.)		demultiplexing

47.21	Of sub-code information	47.49	Control of transducer assembly
47.22	Having location		mechanism
	identification information	47.5	Power control for energy
47.23	For sequencing or switching		producing device
47.24	Between alternative processing	47.51	For storage
	channels	47.52	During multiple system modes
47.25	For gain processing	47.53	Stored and retrieved testing
47.26	Within a frequency band	17.55	signal
		47.54	
47.27	Using a reproduced information		By program or address signal
	of specified preformat,	47.55	During initialization or start-
	header, or reference area		up or changing system mode
47.28	For phase, timing, or rate	52.1	CONTROL STRUCTURE ON STORAGE
	processing		MEDIUM SENSED BY OTHER THAN
47.29	During retrieval at dynamic		TRANSDUCER SUPPORT (E.G.,
	retrieval rate different from		CONDUCTIVE STRIP, NOTCHED EDGE
	storage rate		SENSOR)
47.3	While changing of system mode	53.1	CONDITION INDICATING, MONITORING,
	or dynamic retrieval rate		OR TESTING
47.31	Using program or address	53.11	.Including radiation storage or
	signal		retrieval
47.32	Including static memory	53.12	Having abnormal condition
27.02	accessing		indicating
47.33	Including static memory fill	53.13	Due to unwanted operational
17.55	level monitoring or	33.13	condition of record carrier
	controlling	53.14	Eccentricity or warp
17 21	_		
47.34	Including static memory write	53.15	Defect
45 25	address controlling	53.16	Including storage or
47.35	For sampling, digital to analog		retrieval of auxiliary signal
	or analog to digital	53.17	Defect location indicating
	converting	53.18	System disturbance
47.36	.Mechanism control by the control	53.19	Relative transducer to medium
	signal		misalignment (e.g., relative
47.37	Control of spiral track spacing		tilt)
	(e.g., signal variable pitch)	53.2	Of record carrier
47.38	Control of relative motion	53.21	For protection
	producing mechanism	53.22	By detection of storage medium
47.39	During initialization or		incident radiation
	start-up	53.23	Derived focusing or tracking
47.4	Responsive to change in		related signal
	transduced location	53.24	Having unrecorded location
47.41	Responsive to change in	33.21	indicating
1,.11	transduced information	53.25	Of transducer assembly
	characteristic	33.23	mechanism
47.42	Responsive to stand-by or	F2 06	
47.42		53.26	Energy producing device
47 42	pause mode operation	53.27	By detection of storage
47.43	Having different storage and		medium incident radiation
	retrieval relative motion	53.28	Focusing or tracking servo
47.44	Responsive to abnormal	53.29	Transduced location indicating
	condition	53.3	Of relative motion producing
47.45	By a selected relative motion		mechanism
	error signal	53.31	Of storage or retrieval
47.46	By information signal		information signal
	characteristic	53.32	Dropout indicating
47.47	By program or address signal	53.33	Unwanted signal component
47.48	By synchronous signal		indicating
			<u>-</u>

53.34 53.35	Time based parameterSignal error correcting or	61	STORAGE OF DIRECTLY RETRIEVABLE MODULATED R.F. OR SUPERAUDIBLE
	detecting		CARRIER SIGNAL
53.36	During storage	62	STORAGE OF SIGNAL MODULATING
53.37	Initialization or start-up mode		COMPONENT
	or changing system mode:	63	SOUND REPRODUCTION FOR TOY OR
53.38	.Of transducer assembly mechanism		NOVELTY DEVICE (E.G., TALKING
53.39	Transducer location indicating		DOLL)
53.4	Positioning adjunct	64	.With electrical information
53.41	.Of record carrier		signal processing
53.42	.Having abnormality condition indicating	65	<pre>.Indexing to track (e.g., consecutive)</pre>
53.43	.Of relative motion producing	66	By chance
	mechanism	67	.With beginning or end of cycle
53.44	.Of storage or retrieval		stylus return
	information signal	68	.Manual motion application (e.g.,
53.45	.Initialization or start-up mode		novelty card, hand-held
	or changing system mode		stylus)
59.1	BINARY PULSE TRAIN INFORMATION	69	SYSTEMS OR SUBSYSTEMS COMBINED
	SIGNAL		WITH DIVERSE ART DEVICE
59.11	.Binary signal processing for	70	.For control of diverse art
	controlling recording light		device
	characteristic	71	WITH STYLUS CLEANING OR TREATMENT
59.12	Pulse forming by adjusting		(E.G., GRINDING)
	binary signal phase or	72	WITH STORAGE MEDIUM CLEANING OR
	shifting binary signal pulse		ELECTROSTATIC CHANRGE
59.13	.Selecting from a plurality of		NEUTRALIZATION
	binary processing types	73	.By charge leakage (e.g., ionized
59.14	.Changing a system mode	7.4	particles)
59.15	.Binary signal gain processing	74	.By tone arm attachment
59.16	Within a frequency band	75.1	WITH PARTICULAR CABINET STRUCTURE
59.17	.Binary signal level detecting	75.2	.With mechanism to place disc on
	using a reference signal	76	a turntable
59.18	Plural reference signals	76	.With electrical information
59.19	.Binary signal detecting using a	77.1	signal processing
	clock signal	//.1	.Slotted for edgewise insertion
59.2	.Binary signal phase processing	77.2	of storage discHaving disc stored in
59.21	.Including sampling or A/D converting		protective jacket
59.22	By interpolating or maximum likelihood detecting	78	.With lid-mounted transducer assembly carrier
59.23	.Having specific code or form generation or regeneration	79	.With closure-operated interlock or braking actuator
59.24	<pre>processingDuring storage</pre>	80	<pre>.Particular acoustical structure (e.g., baffle)</pre>
59.25	.Format arrangement processing	81	Having collapsible or
	for auxiliary information		expandable acoustic path
59.26	.Binary signal processing of	82	Having parallel acoustic paths
	sectioned information	83	EDITING OF STORED INFORMATION
59.27	.Binary signal multiplexing or	84	DUPLICATION OR COPYING (E.G.,
	demultiplexing		RERECORDING)
60.01	SIGNAL PROCESSING BY STORAGE AND	85	.To diverse type of storage
	SUBSEQUENT RETRIEVAL (E.G., FREQUENCY SHIFT, DELAY, ETC.)		medium

86	STORAGE OR RETRIEVAL OF SPATIALLY RELATED ACOUSTIC SIGNALS	110.02	Separation into plural polarization component beams
	(E.G., STEREO)	110.03	By diffraction
87	<pre>.Simulated spatial effect (e.g., pseudo-stereo)</pre>	110.04	Using plural polarized or polarizing optical elements
88	.With transformation or	111	Spiral or helical track
00	intentional distortion of	112.01	Having particular optical
	information signal (e.g.,	112.01	element or particular
	preemphasis)		placement thereof in radiation
89	.Quadraphonic		beam path to or from storage
90	Including modulated subchannel		medium
	signal	112.02	Crystal (e.g., liquid, elasto-
91	.Having distinct electrical		optic, photo-refractive, etc.)
	channels	112.03	Diffractive
92	.Including distinct storage	112.04	Plural distinct diffractive
	tracks on record medium		optical elements
93	SYSTEMS HAVING PLURAL PHYSICALLY	112.05	In radiation beam path to
	DISTINCT INDEPENDENT TRACKS ON		storage medium
	A SINGLE STORAGE MEDIUM	112.06	Sectioned optical element
	SURFACE	112.07	Plural diffractive sections
94	.Having layered storage medium	112.08	Lens section
95	.Common time base (i.e.,	112.09	Prism, mirror, or waveguide
	simultaneous)		section
96	.Continuous consecutive storage	112.1	Holographic
	or retrieval of interrupted	112.11	Sectioned optical element
	track for single signal (e.g.,	112.12	Plural diffractive sections
0.17	automatic reversal)	112.13	Lens section
97	Tracks transverse to a motion	112.14	Prism, mirror, or waveguide
0.0	component		section
98	.Indexing to discrete signal	112.15	Holographic
	<pre>tracks (e.g., consecutive, by chance)</pre>	112.16	Polarized or polarizing
99	SPECIFIC DETAIL OF INFORMATION	112.17	Plural distinct polarized
	HANDLING PORTION OF SYSTEM		optical elements
100	.Radiation beam modification of	112.18	Sectioned optical element
	or by storage medium	112.19	Plural polarizing sections
101	Invisible radiation (e.g.,	112.2	Lens section
	electron beam or X-ray)	112.21	Prism, mirror, or waveguide
102	Multiplex	110 00	section
103	Holographic	112.22	Particular optical filter
104	Ribbon light modulator	112.23 112.24	Particular lensPlural distinct lenses
105	Penumbra or push-pull optical	112.24	
	system		Sectioned element
106	Optical feedback	112.26	Plural lens sections
107	Ground noise suppression,	112.27 112.28	Waveguide Prism
	signal envelope, or plural	112.29	Mirror
	optical modulation	113	With medium contacting drum or
108	Color	113	gate in optical system (e.g.,
109.01	Diffractive storage medium		sound head)
	information element	114	Movable roller support for
109.02	Plural elements with distinct		optical path
	diffractive characteristics	115	With driving or stabilizing
110.01	Polarization of or by storage		mechanism
	medium information element	116	Light intensity adjustment or
		-	maintenance

117	Having movable shutter or light gate	130	Sensing of elastic deformation or relaxation of storage
118	With detail, configuration, or adjunct of element having slit or aperture in radiation path	131	<pre>medium (e.g., skid type)Bidirectional information flow (e.g., record/replay</pre>
119	With movement of optical beam (e.g., galvanometer)	132	switching)Recording
120	Having particular radiation sensor	133	With transformation or intentional distortion of
121	<pre>With particular light source (e.g., laser, CRT with phosphor)</pre>		<pre>information signal (e.g., compensation for velocity variation with diameter)</pre>
122	Solid state	134	With particular amplification
123	Glow lamps		characteristic or signal
124.01	With details of electrical signal processing		<pre>control circuitry (e.g., muting)</pre>
124.02	With transducing multiple tracks	135	Specified structure of electrical transducing
124.03	With transducing using plural		assembly
124.03	beams	136	Multichannel (stereo
124.04			cartridge)
124.04	Modulating or demodulating	137	By stress application to
	Integrating or sampling		solid transducing element
124.06	Compressing or decompressing		(e.g., piezoelectric)
124.07	Auxiliary information	138	With adjustable or
	arrangement processing (e.g.,		replaceable stylus coupling
	block headers, subcode, or		structure
	interpolated information,	139	With details of damping or
	etc.)	137	compliance
124.08	Sectioned information	140	Plural styli
	processing (e.g., lengths,	141	Plural alternative or with
104.00	frames, or blocks, etc.)	TAT	signal handling adjunct
124.09	Multiplexing or demultiplexing	142	Stylus controlled optical
124.1	Gain processing	112	element
124.11	Of retrieved signal	143	Electron tube
124.12	Of signals obtained from	144	Electron caseElectret or piezoelectric
	photo-detector components	145	Semiconductive
124.13	With specific frequency or	146	Magnetic field variation
	frequency range	140	(e.g., magnetostrictive)
124.14	Rate, phase, or transient	147	Moving signal coil
	processing	148	Variable reluctance
124.15	Level detecting using	149	Fixed coil surrounding fixed
	reference signal	149	part of magnetic path
125	Having photographic storage	150	
	<pre>medium (e.g., variable density or area)</pre>	150	Capacitive or electrolytic liquid
126	.Electrical modification or	151	Electrostatic or capacitive
	sensing of storage medium	152	Variable resistance
	(e.g., capacitive, resistive,	153	Including treatment to
	electrostatic charge)		facilitate storage (e.g.,
127	.Mechanical modification or		storage medium softening)
	sensing of storage medium	154	Heating (e.g., heated stylus)
128	With electrical information	155	Mechanical conversion to or
	signal processing		from sound
129	From information modulated	156	Including fluid coupling in
	oscillator		force linkage

157	Sound box with mounting structure	191	Storage disc fed to and removed from turntable
158	Acoustical tone arm	192	Plural disc holder having
159	Having plural acoustical		unitary separating structure
	paths	193	Grouped removal with
160	Sound box	100	sequential feed
161	With interchangeable styli	194	Coplanar storage
162		195	Both sides of disc used
102	Including stylus pivoted from fixed casing	196	Separate motors operate
163	With sound modification	190	
			turntable and disc change mechanism
164	Convertible between lateral	107	
	and perpendicular modulation	197	Plural turntables
1.65	modes	198	Plural tone arms
165	Perpendicular mechanical	199	Both sides of disc used
	modulation	200	By inverting disc
166	Recording	201	Discs sequentially removed from
167	With mechanical		turntable
	amplification (e.g.,	202	Discs sequentially fed to
	frictional coupling)		turntable
168	Floating weight	203	Tone arm set down adjustment
169	Lateral mechanical modulation	204	By edge controlled feeding of
170	Stylus holder or shield		disc
171	With structure to interchange	205	With feed cooperating
	styli		structure on spindle
172	By replacement	206	By center hold feeding of disc
173	Stylus		(e.g., spindle drop)
174	.Including signal modification	207	Support mechanism adapter for
175	Frequency dependent (e.g.,		large hole records on small
1 /J			
175			
176	separation) DYNAMIC MECHANISM SUBSYSTEM	208	hole spindles
176	separation) DYNAMIC MECHANISM SUBSYSTEM	208	
176 177	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium	208	hole spindlesHaving specified spindle structure
176	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage	209	hole spindlesHaving specified spindle structureUmbrella type
176 177	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record		hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector
176 177 178.01	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer)	209 210	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector lever
176 177 178.01	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element	209 210 211	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizer
176 177 178.01 179 180	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage elementFlexible disc	209 210	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g.,
176 177 178.01	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for	209 210 211	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc
176 177 178.01 179 180 181	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable	209 210 211 212	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer)
176 177 178.01 179 180 181	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off	209 210 211	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage
176 177 178.01 179 180 181	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to	209 210 211 212	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect
176 177 178.01 179 180 181	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of	209 210 211 212 213	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect tracking
176 177 178.01 179 180 181 182 183	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer	209 210 211 212 213	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element
176 177 178.01 179 180 181	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by	209 210 211 212 213	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer
176 177 178.01 179 180 181 182 183	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by sensing of disc (e.g., disc or	209 210 211 212 213 214 215	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assembly
176 177 178.01 179 180 181 182 183	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer)Cylindrical storage elementFlexible discStack height adjustment for tone arm or turntableNumerical count shut-offCam shaft transverse to turntable spindle axis of record changerTone arm position control by sensing of disc (e.g., disc or hole size)	209 210 211 212 213	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down
176 177 178.01 179 180 181 182 183	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer)Cylindrical storage elementFlexible discStack height adjustment for tone arm or turntableNumerical count shut-offCam shaft transverse to turntable spindle axis of record changerTone arm position control by sensing of disc (e.g., disc or hole size)Disc size sensor on or using	209 210 211 212 213 214 215 216	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down control
176 177 178.01 179 180 181 182 183	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by sensing of disc (e.g., disc or hole size) Disc size sensor on or using tone arm	209 210 211 212 213 214 215	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down controlBy disc sensing (e.g., by
176 177 178.01 179 180 181 182 183	Separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by sensing of disc (e.g., disc or hole size) Disc size sensor on or using tone arm Stepped tone arm stop element	209 210 211 212 213 214 215 216 217	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down controlBy disc sensing (e.g., by sensed disc or hole size)
176 177 178.01 179 180 181 182 183	separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by sensing of disc (e.g., disc or hole size) Disc size sensor on or using tone arm Stepped tone arm stop element Disc size sensor in feed path	209 210 211 212 213 214 215 216	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down controlBy disc sensing (e.g., by sensed disc or hole size)Having groove engaging driving
176 177 178.01 179 180 181 182 183	Separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by sensing of disc (e.g., disc or hole size) Disc size sensor on or using tone arm Stepped tone arm stop element Disc size sensor at turntable	209 210 211 212 213 214 215 216 217 218	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down controlBy disc sensing (e.g., by sensed disc or hole size)Having groove engaging driving element
176 177 178.01 179 180 181 182 183 184 185 186 187	Separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by sensing of disc (e.g., disc or hole size) Disc size sensor on or using tone arm Stepped tone arm stop element Disc size sensor at turntable position	209 210 211 212 213 214 215 216 217	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down controlBy disc sensing (e.g., by sensed disc or hole size)Having groove engaging driving elementWith drive transverse to
176 177 178.01 179 180 181 182 183 184 185 186 187 188	Separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by sensing of disc (e.g., disc or hole size) Disc size sensor on or using tone arm Stepped tone arm stop element Disc size sensor at turntable position Turntable speed control	209 210 211 212 213 214 215 216 217 218	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down controlBy disc sensing (e.g., by sensed disc or hole size)Having groove engaging driving elementWith drive transverse to storage track during storage
176 177 178.01 179 180 181 182 183 184 185 186 187	DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer)Cylindrical storage elementFlexible discStack height adjustment for tone arm or turntableNumerical count shut-offCam shaft transverse to turntable spindle axis of record changerTone arm position control by sensing of disc (e.g., disc or hole size)Disc size sensor on or using tone armStepped tone arm stop elementDisc size sensor at turntable positionTurntable speed controlBy sensing of disc (e.g., disc	209 210 211 212 213 214 215 216 217 218 219	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down controlBy disc sensing (e.g., by sensed disc or hole size)Having groove engaging driving elementWith drive transverse to storage track during storage or retrieval
176 177 178.01 179 180 181 182 183 184 185 186 187 188	Separation) DYNAMIC MECHANISM SUBSYSTEM .Having stationary storage medium .Access of multiple storage elements (e.g., record changer) Cylindrical storage element Flexible disc Stack height adjustment for tone arm or turntable Numerical count shut-off Cam shaft transverse to turntable spindle axis of record changer Tone arm position control by sensing of disc (e.g., disc or hole size) Disc size sensor on or using tone arm Stepped tone arm stop element Disc size sensor at turntable position Turntable speed control	209 210 211 212 213 214 215 216 217 218	hole spindlesHaving specified spindle structureUmbrella typeHaving shoulder and ejector leverWith edge stabilizerAuxiliary structure (e.g., shut-off preventer, disc spacer) .Additional motion of storage element support to effect trackingCylindrical storage element .Having power driven transducer assemblyHaving tone arm set-down controlBy disc sensing (e.g., by sensed disc or hole size)Having groove engaging driving elementWith drive transverse to storage track during storage

221	With additional drive (e.g.,	251	Having application of
	scanning, restoring, or	252	counterbalancing force
222	return)	252	Lateral (e.g., antiskating)
	Having pivoted tone arm	253	By resilient force element
223	By lead screw		(e.g., spring)
224	With passive linear tracking	254	Specified weight mounting
225	Restoring after passive tracking	255	Having specified bearing structure
226	Responsive to transducer	256	Mechanical details of cartridge
	support condition (e.g.,		mounting
	movement or position)	257	Rest
227	Numerical count replay	258	. Specific detail of storage
228	Controllable position	230	medium support or motion
229	Turntable mounted template		production
230	Power cueing (i.e., engage/	259	For endless web looped about
250	disengage)	237	
231	.Mechanism responsive to control		<pre>plural rotatable mounts (e.g., belt)</pre>
231	structure on storage medium	260	For cylinder
	sensed by transducer assembly	261	For pliable (e.g., floppy) disc
	support (e.g., trip device)	262	With storage medium removal
232	With turntable braking (e.g.,	202	adjunct
	velocity or reverse	263	Mounting structure for support
	responsive)		or motion producing assembly
233	.Mechanism condition or storage		(e.g., vibration damping
	medium responsive control	264	Turntable
234	With turntable braking (e.g.,	265	With auxiliary turntable
	tone arm position responsive)	266	Driving mechanism
235	With stopping of motor	267	Speed changing
236	Adjustable	268	Braking
237	With electrical control of	269	Bearing structure
20,	brake	270	_
238	End limit sensor coupled with	270	Disc holding or locating
250	tone arm	071	(e.g., spindle structure)
239		271	With detail of storage medium
	Speed		contact structure on turntable
240	Variable radius compensation	0.00	surface
	(e.g., constant interaction	272	STORAGE MEDIUM STRUCTURE
0.41	speed)	273	.Combined with diverse art
241	Self-responsive (e.g.,		structure
	governor)	274	.Composite (e.g., package with
242	Antiskating		preview record)
243	Energizing circuit	275.1	.Optical track structure (e.g.,
244	.Specific detail of transducer		phase or diffracting
	assembly support structure		structure, etc.)
0.45	(e.g., tone arm)	275.2	Erasable, reversible or re-
245	With manual tone arm		recordable
	displacement adjunct (e.g.,	275.3	Track data format/layout
	cueing)	275.4	Pit/bubble/groove structure
246	With viscous limiting of		specifies
	motion (e.g., rate damping)	275.5	Protection (e.g., preventing
247	Vibration or resonance		damage to medium, etc.)
	<pre>suppression (e.g., damping)</pre>	276	.Electrical track structure
248	By viscous damping	277	.Special groove (e.g., particular
249	Having linear guide		groove shape)
250	Pivoted arm with tracking path	278	Groove acts as control system
	compensation		signal

279	Guide during storage or
	retrieval
280	.Specific disc profile
281	With interdisc coupling
282	.Specified center hole or
	locating structure
283	.Layered (e.g., permanent
	protective layer)
284	Radiation beam modified or
	<pre>controlling (e.g.,</pre>
	photosensitve, optical track)
285	With mask
286	Laminated or unified discrete
	layers
287	.Flexible
288	.Specified material
289	.Adjuncts or adapters
290	For central area of disc (e.g.,
	hole size or drive sticker)
291	Protectors
292	MISCELLANEOUS

FOREIGN ART COLLECTIONS

FOR 000 CLASS-RELATED FOREIGN DOCUMENTS

Any foreign patents or non-patent literature from subclasses that have been reclassified have been transferred directly to FOR Collection listed below. These Collections contain ONLY foreign patents or non-patent literature. The parenthetical references in the Collection titles refer to the abolished subclasses from which these Collections were derived.

FOR 100 SIGNAL PROCESSING BY STORAGE AND SUBSEQUENT RETRIEVAL (E.G., FREQUENCY SHIFT, DELAY, ETC.) (369/60)

SPECIFIC DETAIL OF INFORMATION HANDLING PORTION OF SYSTEM (369/99)

.Radiation beam modification of or by storage medium (369/100)

FOR 101 ..With details of electrical signal processing (369/124)

FOR 102 CONTROL OF STORAGE OR RETRIEVAL

BY A SIGNAL TO BE RECORDED OR

REPRODUCED (369/47)

FOR 103 CONTROL OF INFORMATION SIGNAL CHANNEL (369/48)

FOR 104 OF PLURAL INTERRELATED CHANNELS (369/49)

FOR 105 MECHANISM CONTROL BY INFORMATION SIGNAL (E.G., VOICE RESPONSIVE) (369/50)

FOR 106 CONTROL OF SPIRAL TRACK SPACING
(E.G., SIGNAL VARIABLE PITCH)
(369/51)

FOR 107 CONTROL STRUCTURE ON STORAGE

MEDIUM SENSED BY OTHER THAN

TRANSDUCER SUPPORT (E.G.,

CONDUCTIVE STRIP, NOTCHED EDGE

SENSOR) (369/52)

FOR 108 WITH CONDITION INDICATING (E.G., MONITORING) OR TESTING (369/53)

FOR 109 WITH RADIATION STORAGE OR RETRIEVAL (369/54)

FOR 110 OF TRANSDUCER (369/55)

FOR 111 LOCATION ON STORAGE MEDIUM (369/

FOR 112 POSITIONING ADJUNCT (E.G., INDEXING) (369/57)

FOR 113 OF RECORD CARRIER (369/58)

FOR 114 WITH BINARY PULSE TRAIN
INFORMATION SIGNAL (369/59)

SPECIFIC DETAIL OF INFORMATION HANDLING PORTION OF SYSTEM (369/99)

.Radiation beam modification of or by storage (369/100)

FOR 115 ..With diffraction (e.g., pits, grating (369/109)

FOR 116 ...By polarization (369/110)

FOR 117 ..With particular imaging element (369/112)

FOR 118 STORAGE DIFFERENT FROM RETRIEVAL

(E.G., OPTICAL RECORDING AND

MAGNETIC REPRODUCTION) (369/
13)

FOR 119 OPERATOR-ACTUATED REMOTE CONTROL
OR INFORMATION LOCATION (369/
24)

FOR 120 .Dictation or transcribing (369/ 25)

FOR 121 .. Privacy (369/26)

FOR 122 ..With access to or marking of specified location (e.g., indexing) (369/27)

FOR 123 ...By stored additional signal (e.g., tone) (369/28)

- FOR 125 .Selective addressing of storage medium (e.g., programmed access, "juke box") (369/30)
- FOR 126 ..Novelty device (e.g., talking doll) (369/31)
- FOR 127 ..With specified electrical information signal processing (369/32)
- FOR 128 ..With specified electrical control signal processing (369/33)
- FOR 129 ...Plural storage medium elements (369/34)
- FOR 130 ..Plural nontranslating storage elements (e.g., in situ) (369/35)
- FOR 131 ..With unitary plural disc carrier (369/36)
- FOR 132 ...Radial array (369/37)
- FOR 133 ... Moving linear array (369/38)
- FOR 134 ...Scanning turntable (369/39)
- FOR 135 ..By manually actuated mechanism for movement of tone arm (369/40)
- FOR 136 ..Of track on single storage medium (369/41)
- FOR 137 .By mechanical linkage (369/42)

 DYNAMIC MECHANISM SUBSYSTEM (369/
- 176)
 FOR 138 .Access of multiple storage
 elements (e.g., record
- elements (e.g., record changer) (369/178)